

Σελίδα προϊόντος



VLIFE LEGRAND

Valena™ IN'MATIC Μηχανισμοί - Ανιχνευτές Κίνησης χωρίς Ουδέτερο

ΚΩΔ. 752070 | EAN. 3414970620934

Valena™ IN'MATIC Μηχανισμοί - Ανιχνευτές Κίνησης χωρίς ουδέτερο. Ακροδέκτες με βίδες. Με ενσωματωμένη προστασία από υπέρταση και βραχυκύκλωμα.

Εγγύηση 2 χρόνια

[> Επισκεφθείτε τον e-κατάλογο](#)

Κύρια περιγραφή:

Valena™ IN'MATIC Μηχανισμοί - Ανιχνευτές Κίνησης χωρίς ουδέτερο. Ακροδέκτες με βίδες. Με ενσωματωμένη προστασία από υπέρταση και βραχυκύκλωμα.

Τεχνικά Χαρακτηριστικά

Model	Movement sensor
With DALI interface	No
Constant light control	Yes
HVAC-control	No
Forced switch off	Yes
Animal zone	No
Creep-under protection	No
Background monitoring	No
Networkable	No
Optimum mounting height	1.2 m
Staircase light controller	Yes
Bridging switch	No
Max. reach sideways	6 m
Max. reach frontally	8 m
Diameter reach on floor	6 m
Suitable for wireless transmission	No

RAL-number (similar)	7370
Transparent	No
Degree of protection (IP)	IP40
Impact strength	IK04
Voltage type	AC
Frequency	47-63 Hz
Nominal voltage	230-230 V
Min. switch-on time	10 s
Max. duty cycle	10 min
Detection angle horizontal	120-120 °
Response value luminosity	5-1275 lx
Max. switching power	250 W
Temperature	-5-45 °C
Max. starting current	0.4 A
Control current	0.4 mA
Substation input	No

Remote operation	No
With remote control	No
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
With signal unit	Yes
Teach-function for response value luminosity	No
Dim function with dimmer basic element	No
Mounting method	Flush-mounted
Connection type	Screwed terminal
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Anti-bacterial treatment	No
Colour	Grey

With alarm function	No
With acoustic sensor	No
Width	74.7 mm
Height	74.7 mm
Depth	32.1 mm
Built-in depth	32.1 mm
With connection cable	No
Connection cable length	0 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Operating / setting temperature	-5-45 °C
Storage temperature	-20-70 °C
Terminals capacity	2.5-2.5 mm ²
Auto switch	Yes

Έντυπα

Τεχνικά εγχειρίδια

 F01970EN-01.pdf | PDF (2.01Mo)


 LE07972AD.pdf | PDF (1.26Mo)

 LE07972AE.pdf | PDF (0.58Mo)

CAD & σχεδιαστικά / BIM

 752070_AIICATPart.stp | IFC (20.84Mo)

Σελίδες καταλόγου

 GenCat2020_21_p 252.pdf | PDF (0.12Mo)