

# Σελίδα προϊόντος



## VLIFE LEGRAND

Valena™ IN'MATIC Μηχανισμοί - ΑνιχνευτέςΚίνησης με Ουδέτερο

ΚΩΔ. 752073 | EAN. 3414970620972

Ανιχνευτής Κίνησης με ουδέτερο. Ακροδέκτες με βίδες. Με ενσωματωμένη προστασία από υπέρταση και βραχυκύκλωμα. Συμβατός με κάθε τύπο λαμπτήρων. Οριζόντια γωνία ανίχνευσης 180°, εμβέλεια 8m.

Εγγύηση 2 χρόνια

> [Επισκεφθείτε τον e-κατάλογο](#)

## Κύρια περιγραφή:

Ανιχνευτής Κίνησης με ουδέτερο. Ακροδέκτες με βίδες. Με ενσωματωμένη προστασία από υπέρταση και βραχυκύκλωμα. Συμβατός με κάθε τύπο λαμπτήρων. Οριζόντια γωνία ανίχνευσης 180°, εμβέλεια 8m.

## Τεχνικά Χαρακτηριστικά

Model	Movement sensor
Sensor type	Passive infrared
With DALI interface	No
Constant light control	No
HVAC-control	No
Forced switch off	No
Animal zone	No
Creep-under protection	No
Background monitoring	No
Networkable	No
Scan angle	120 °
Optimum mounting height	1.2 m
Staircase light controller	Yes
Bridging switch	No
Max. reach sideways	6 m
Max. reach frontally	8 m

Transparent	No
Degree of protection (IP)	IP20
Impact strength	IK02
Voltage type	AC
Frequency	50-60 Hz
Nominal voltage	230-230 V
Min. switch-on time	10 s
Max. duty cycle	10 min
Switch-off delay	0 s
Switching-on delay	0 s
Detection angle horizontal	-60-60 °
Response value luminosity	5-1275 lx
Max. switching power	400 W
Temperature	0-40 °C
Number of switching zones	1
Max. starting current	1.8 A

Diameter reach on floor	6 m
Suitable for wireless transmission	No
Remote operation	No
With remote control	No
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
With signal unit	No
Teach-function for response value luminosity	No
Dim function with dimmer basic element	No
Mounting method	Flush-mounted
Suitable for ceiling mounting	No
Suitable for wall mounting	Yes
Connection type	Screwed terminal
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Anti-bacterial treatment	No
Colour	Other

Control current	0.2 mA
Substation input	No
With alarm function	No
With acoustic sensor	No
Width	75 mm
Height	75 mm
Depth	51.5 mm
Built-in depth	32 mm
Min. depth of built-in installation box	40 mm
With connection cable	No
Connection cable length	0 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Operating / setting temperature	-5-35 °C
Storage temperature	-10-70 °C
Terminals capacity	2.5-2.5 mm <sup>2</sup>
Label holder fitted	No
Auto switch	Yes

## Έντυπα

### Τεχνικά εγχειρίδια

F01966EN-04.pdf | PDF (1.11Mo)

LE07972AD.pdf | PDF (1.26Mo)

LE07972AE.pdf | PDF (0.58Mo)

### CAD & σχεδιαστικά / BIM

752073\_AllCATPart.stp | IFC (17.75Mo)

### Σελίδες καταλόγου

GenCat2020\_21\_p 252.pdf | PDF (0.12Mo)