

Σελίδα προϊόντος



VALENA LIFE LEGRAND

Valena Life™ πρίζα σούκο με USB φόρτισης τύπου C σε λευκό χρώμα

ΚΩΔ. 753135 | EAN. 3414971364059

Valena Life™ - Πρίζα 2Π + Γ και Φόρτισης USB Πρίζα 2Π+Γ ασφαλείας + USB C φόρτισης. Παραδίδεται με ενσωματωμένο πλακίδιο. Χρώμα: White.

Εγγύηση 2 χρόνια

> [Επισκεφθείτε τον e-κατάλογο](#)

Κύρια περιγραφή:

Valena Life™ - Πρίζα 2Π + Γ και Φόρτισης USB Πρίζα 2Π+Γ ασφαλείας + USB C φόρτισης. Παραδίδεται με ενσωματωμένο πλακίδιο. Χρώμα: White.

Τεχνικά Χαρακτηριστικά

Model	Socket outlet CEE 7/3 (type F)
Protective contact	Other
Number of active contacts (round)	1
Number of active contacts (flat)	0
With signal lamp	No
Number of ports USB-A	0
Number of ports USB-C	1
Number of units	1
Number of modules (module system)	0
Number of socket outlets switchable	0
Number of phases	1
Imprint/indication	None
Connection type	Push-in clamp
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No

Anti-bacterial treatment	No
With loop through function	No
With on/off switch	No
Colour of switch operator	White
Rotated central insert	No
Nominal current	16 A
Nominal voltage	250 V
Frequency	50-60 Hz
Suitable for degree of protection (IP)	IP40
Impact strength	IK04
Device width	75 mm
Device height	75 mm
Device depth	41.5 mm
Min. depth of built-in installation box	40 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No

Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Over voltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	Other
Mounting method	Flush-mounted
Type of fastening	Mounting with claw and screw
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy

Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	31.5 mm
Operating / setting temperature	-5-35 °C
Storage temperature	-10-70 °C
Type of voltage	AC
Power Delivery	No
USB Output Power	7.5 W
Terminal marking indication	Yes
Prewired	No
Terminals capacity	2.5-2.5 mm ²
Cable nature for connection	Flexible or rigid
Cable section	2.5-2.5 mm ²
Cable support	Other
Cover	Central cover plate
Connected object	No

Έντυπα

Τεχνικά εγχειρίδια

F02797EN-01.pdf | PDF (0.26Mo)

Πρότυπα & πιστοποιητικά

OC / CB-FR_705589

Σελίδες καταλόγου

GenCat2020_21_p 266.pdf | PDF (0.63Mo)