

# Σελίδα προϊόντος



## VALENA LEGRAND

Valena™ διακόπτης κομμουτατέρ σε χρώμα αλουμίνιο  
ΚΩΔ. 770105 | EAN. 3245067701058

Διακόπτης κομμουτατέρ 10 A - 250 V~ Χρώμα: αλουμίνιο

Εγγύηση 2 χρόνια

> [Επισκεφθείτε τον e-κατάλογο](#)

## Κύρια περιγραφή:

Διακόπτης κομμουτατέρ 10 A - 250 V~ Χρώμα: αλουμίνιο

## Τεχνικά Χαρακτηριστικά

|                          |  |
|--------------------------|--|
| Wiring system            | Off switch 1-pole                      |
| Method of operation      | Rocker/button                          |
| Assembly arrangement     | Basic element with central cover plate |
| Push button switch       | No                                     |
| Number of rockers        | 2                                      |
| Mounting method          | Flush-mounted                          |
| Type of fastening        | Mounting with claw and screw           |
| With mounting plate      | Yes                                    |
| Material                 | Plastic                                |
| Material quality         | Thermoplastic                          |
| Halogen free             | Yes                                    |
| Anti-bacterial treatment | No                                     |
| Surface protection       | Lacquered                              |
| Surface finishing        | Glossy                                 |
| Colour                   | Aluminium                              |
| RAL-number (similar)     | 7040                                   |

|   |       |
|---|-------|
| Impact strength                         | IK04  |
| Nominal voltage                         | 250 V |
| Rated current                           | 10 A  |
| Switching current for fluorescent lamps | 10 AX |
| Feedback-signal contact                 | No    |
| Connection type                         | Other |
| Heating switch                          | No    |
| Washing machine switch                  | No    |
| Device width                            | 71 mm |
| Device height                           | 71 mm |
| Device depth                            | 37 mm |
| Built-in depth                          | 21 mm |
| Min. depth of built-in installation box | 30 mm |
| Compatible with Apple HomeKit           | No    |
| Compatible with Google Assistant        | No    |
| Compatible with Amazon Alexa            | No    |
| IFTTT support available                 | No    |

|  |           |
|--|-----------|
| Colour of switch operator              | Aluminium |
| Label space/information surface        | No        |
| Illumination                           | No        |
| Function lighting                      | Other     |
| Type of lighting                       | Other     |
| Suitable for degree of protection (IP) | IP31      |


|                                 |                         |
|---------------------------------|-------------------------|
| Operating / setting temperature | -5-40 °C                |
| Storage temperature             | -25-40 °C               |
| Type of voltage                 | AC                      |
| Supply frequency                | 50-60 Hz                |
| Cable section                   | 2.5-2.5 mm <sup>2</sup> |

## Έντυπα

### Τεχνικά εγχειρίδια

 [N453090477-7.pdf](#) | PDF (5.07Mo)

### Σελίδες καταλόγου

 [GenCat2020\\_21\\_p 271.pdf](#) | PDF (0.3Mo)