

Σελίδα προϊόντος



VALENA LEGRAND

Valena™ πρίζα σούκο ασφαλείας με καπάκι σε χρώμα αλουμίνιο

ΚΩΔ. 770122 | EAN. 3245067701225

Πρίζα 2Π+Γ τύπου σούκο ασφαλείας με καπάκι 16 A - 250 V~ Ακροδέκτες με βίδες Κατηγορία IP 2X Χρώμα : αλουμίνιο

Εγγύηση 2 χρόνια

> [Επισκεφθείτε τον e-κατάλογο](#)

Κύρια περιγραφή:

Πρίζα 2Π+Γ τύπου σούκο ασφαλείας με καπάκι 16 A - 250 V~ Ακροδέκτες με βίδες Κατηγορία IP 2X Χρώμα : αλουμίνιο

Τεχνικά Χαρακτηριστικά

Model	Socket outlet CEE 7/3 (type F)
Protective contact	Other
Number of active contacts (round)	1
Number of active contacts (flat)	0
With complementary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of units	1
Number of socket outlets switchable	0
Number of phases	1
Imprint/indication	None
Connection type	Screwed terminal
With hinged lid	Yes
With enhanced contact protection	Yes
Label space/information surface	No
Colour	Aluminium
RAL-number (similar)	7040

Surface protection	Lacquered
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	No
Colour of switch operator	Aluminium
Rotated central insert	No
Nominal current	16 A
Nominal voltage	250 V
Frequency	50-60 Hz
Suitable for degree of protection (IP)	IP21
Degree of impact strength (IK)	IK04
Device width	71 mm
Device height	71 mm
Device depth	51 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No

Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Over voltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	No special power supply
Mounting method	Flush-mounted
Type of fastening	Mounting with claw and screw
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes


Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	31 mm
Operating / setting temperature	-5-40 °C
Storage temperature	-5-40 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Flexible or rigid
Cable section	2.5-2.5 mm ²
Cable support	Other
Cover	Central cover plate
Connected object	No

Έντυπα

Τεχνικά εγχειρίδια

 F02064EN-00.pdf | PDF (0.81Mo)

Πρότυπα & πιστοποιητικά

 MEEI-UP 69265742 0002 | (1.32Mo)

 AENOR-030/001756 | (0.47Mo)