

# Σελίδα προϊόντος



## VALENA LEGRAND

Valena™ Πρίζα πληροφορικής- ΚΑΤ 6- RJ45 UTP 2 ΕΞ-  
χρώμα κρεμ

ΚΩΔ. 774147 | EAN. 3245067741474

Πρίζα RJ45 κατ.6 UTP, 2 έξοδοι Σύμφωνα με τα πρότυπα ISO 11801, EN 50173 και EIA/TIA 568 Πρίζα γρήγορης σύνδεσης χωρίς χρήση εργαλείου Με διπλό χρωματικό κώδικα και αρίθμηση. Στήριξη με νύχια Χρώμα: κρεμ

Εγγύηση 2 χρόνια

> [Επισκεφθείτε τον e-κατάλογο](#)

## Κύρια περιγραφή:

Πρίζα RJ45 κατ.6 UTP, 2 έξοδοι Σύμφωνα με τα πρότυπα ISO 11801, EN 50173 και EIA/TIA 568 Πρίζα γρήγορης σύνδεσης χωρίς χρήση εργαλείου Με διπλό χρωματικό κώδικα και αρίθμηση. Στήριξη με νύχια Χρώμα: κρεμ

## Τεχνικά Χαρακτηριστικά

Surface mounting	No	With dust cover	No
Flush-mounted installation	Yes	Mechanical coding	No
Duct installation	No	Colour coding	Yes
Floor box/subfloor mounted	No	Device width	71 mm
Type of fastening	Other	Device height	71 mm
Assembly arrangement	Basic element with central cover plate	Device depth	36 mm
Type of connector	RJ45 8(8)	Built-in depth	26.2 mm
With buses/couplings	Yes	Operating / setting temperature	-5-35 °C
Suitable for number of connectors	2	Storage temperature	-10-70 °C
Category	6	Terminal marking indication	Yes
Colour	Other	Halogen free	Yes
RAL-number	1013	Antimicrobial treatment	No
Connection type	Insulation displacement connector	Mounting method	Flush-mounted
Shielded buses	No	Tube diameter for wall mounted product	0-0 mm
Separate earthing connection	No	Maximum Input cable diameter	9 mm

With label space	No
Separate strain relief	No
Mounting method shielding connection	None
Outlet direction	Inclined











Entry membrane gland type	Not applicable
Vertical fixing center distance	0-0 mm
Horizontal fixing center distance	0-0 mm
Cable support	Not applicable

## Έντυπα

### Τεχνικά εγχειρίδια

 078506129D.pdf | PDF (1.63Mo)

### Πρότυπα & πιστοποιητικά

-  AoC-PL2\_C6\_UTP\_32886\_ac1191056 | (0.06Mo)
-  AoC-PL3\_Cat6\_UTP\_32754\_ac1181026 | (0.07Mo)
-  AoC-CL4\_Cat6\_UTP\_32866\_ac1181047 | (0.08Mo)
-  AoC-Ac Delta Force 4PPoE 2019-677 | (0.08Mo)
-  AoC-SA51\_SB51\_ac109587 | (0.06Mo)
-  LGRP-01037-V01.01-EN.pdf | PDF (0.6Mo)
-  AoC-CL2\_C6\_UTP\_32886\_ac1191057 | (0.06Mo)
-  AoC-CL4\_Cat6\_UTP\_32754\_ac1181046 ( | (0.08Mo)
-  AoC-CL2\_Cat6UTP3275432861ac1181025 | (0.07Mo)
-  AoC-PL2\_Cat6\_UTP\_32754\_ac1181024 | (0.07Mo)