

Σελίδα προϊόντος



VALENA LEGRAND

Valena™ - Ανιχνευτής Κίνησης 1000W με Ουδέτερο, λευκό

ΚΩΔ. 774269 | EAN. 3414970978219

Valena™ - Ανιχνευτής Κίνησης 1000W με Ουδέτερο 1000 W για λαμπτήρες πυρακτώσεως και ιωδίνης 230 V 500VA για λαμπτήρες ιωδίνης ΠΧΤ με ηλεκτρονικό ή επαγωγικό μετασχηματιστή.

Εγγύηση 2 χρόνια

> [Επισκεφθείτε τον e-κατάλογο](#)

Κύρια περιγραφή:

Valena™ - Ανιχνευτής Κίνησης 1000W με Ουδέτερο 1000 W για λαμπτήρες πυρακτώσεως και ιωδίνης 230 V 500VA για λαμπτήρες ιωδίνης ΠΧΤ με ηλεκτρονικό ή επαγωγικό μετασχηματιστή.

Τεχνικά Χαρακτηριστικά

| | |
|----------------------------|------------------|
| Model | Movement sensor |
| Sensor type | Passive infrared |
| With DALI interface | No |
| Constant light control | No |
| HVAC-control | No |
| Forced switch off | No |
| Animal zone | No |
| Creep-under protection | No |
| Background monitoring | No |
| Networkable | No |
| Optimum mounting height | 1.2 m |
| Staircase light controller | Yes |
| Bridging switch | No |
| Max. reach sideways | 6 m |
| Max. reach frontally | 8 m |

| | |
|-----------------------------------|-----------|
| Degree of protection (IP) | IP41 |
| Degree of impact strength (IK) | IK04 |
| Voltage type | AC |
| Frequency | 47-63 Hz |
| Nominal voltage | 230-230 V |
| Min. switch-on time | 10 s |
| Max. duty cycle | 10 min |
| Switch-off delay | 0 s |
| Switching-on delay | 0 s |
| Detection angle horizontal | 120-120 ° |
| Pivoting range sensor, horizontal | 0-0 ° |
| Pivoting range sensor, vertical | 0-0 ° |
| Response value luminosity | 5-1275 lx |
| Max. switching power | 1000 W |
| Suitable for C-load | Yes |

| | |
|--|------------------|
| Diameter reach on floor | 6 m |
| Suitable for wireless transmission | No |
| Remote operation | No |
| Supplied remote control | No |
| Response value sensitivity adjustable | No |
| Response value luminosity adjustable | Yes |
| With signal unit | No |
| Teach-function for response value luminosity | No |
| Dim function with dimmer basic element | No |
| Mounting method | Flush-mounted |
| Connection type | Screwed terminal |
| Material | Plastic |
| Material quality | Thermoplastic |
| Halogen free | Yes |
| Surface protection | Lacquered |
| Surface finishing | Glossy |
| Antimicrobial treatment | No |
| Colour | White |
| RAL-number (similar) | 9003 |
| Transparent | No |

| | |
|----------------------------------|-------------------------|
| Temperature | -5-45 °C |
| Number of switching zones | 1 |
| Substation input | No |
| With alarm function | No |
| With acoustic sensor | No |
| Width | 71 mm |
| Height | 71 mm |
| Depth | 34 mm |
| Built-in depth | 34 mm |
| With connection cable | No |
| Connection cable length | 0 mm |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |
| Operating / setting temperature | -5-45 °C |
| Storage temperature | -20-70 °C |
| Terminals capacity | 2.5-2.5 mm ² |
| Auto switch | Yes |

Έντυπα

Τεχνικά εγχειρίδια



LE09812AA.pdf | PDF (1.09Mo)

CAD & σχεδιαστικά / BIM



774169_AllCATPart.stp | IFC (16.16Mo)