

# Σελίδα προϊόντος



## VALENA LEGRAND

Valena™ πρίζα σούκο ασφαλείας σε λευκό χρώμα

ΚΩΔ. 774421 | EAN. 3245067744215

Πρίζα 2Π+Γ τύπου σούκο ασφαλείας 16 A - 250 V~  
Ακροδέκτες με βίδες Κατηγορία IP 2X Χρώμα : λευκό

Εγγύηση 2 χρόνια

> [Επισκεφθείτε τον e-κατάλογο](#)

## Κύρια περιγραφή:

Πρίζα 2Π+Γ τύπου σούκο ασφαλείας 16 A - 250 V~ Ακροδέκτες με βίδες Κατηγορία IP 2X Χρώμα : λευκό

## Τεχνικά Χαρακτηριστικά

Model	Socket outlet CEE 7/3 (type F)
Protective contact	Other
Number of active contacts (round)	1
Number of active contacts (flat)	0
With complementary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of units	1
Number of socket outlets switchable	0
Number of phases	1
Imprint/indication	None
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No
Colour	White
RAL-number (similar)	9003

Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	No
Colour of switch operator	White
Rotated central insert	No
Nominal current	16 A
Nominal voltage	250 V
Frequency	50-60 Hz
Suitable for degree of protection (IP)	IP21
Degree of impact strength (IK)	IK04
Device width	71 mm
Device height	71 mm
Device depth	43 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No

<b>Metallic colour</b>	No
<b>Transparent</b>	No
<b>Lockable</b>	No
<b>Eject-mechanism</b>	No
<b>Insulated mounting</b>	No
<b>With function lighting</b>	No
<b>With orientation lighting</b>	No
<b>Over voltage protection</b>	No
<b>Fault current protection</b>	No
<b>With miniature fuse</b>	No
<b>Special power supply</b>	No special power supply
<b>Mounting method</b>	Flush-mounted
<b>Type of fastening</b>	Mounting with claw and screw
<b>Material</b>	Plastic
<b>Material quality</b>	Thermoplastic
<b>Halogen free</b>	Yes

<b>Compatible with Google Assistant</b>	No
<b>IFTTT support available</b>	No
<b>With Wi-Fi signal repeater</b>	No
<b>With built-in bluetooth speaker</b>	No
<b>For heavy conditions according to VDE</b>	No
<b>Built-in depth</b>	31 mm
<b>Operating / setting temperature</b>	-5-40 °C
<b>Storage temperature</b>	-5-40 °C
<b>Voltage type</b>	AC
<b>Power Delivery</b>	No
<b>Cable nature for connection</b>	Flexible or rigid
<b>Cable section</b>	2.5-2.5 mm <sup>2</sup>
<b>Cable support</b>	Other
<b>Cover</b>	Central cover plate
<b>Connected object</b>	No

## Έντυπα

### Τεχνικά εγχειρίδια

F02064EN-00.pdf | PDF (0.81Μο)

### Πρότυπα & πιστοποιητικά

MEEI-UP 69265742 0002

AENOR-030/001756